Size:

Weight:

Battery Chargers

Battery Charger,

DCP2-1210

Battery Charger, DCP2-1205 Main function: The DCP2 can be applied as battery charger or as a universal DC voltage supply. Input voltage: 1 x 230V AC ±15% 47...63Hz Output voltage: 12V DC (adjustable 11.8...13.8V DC) Output current: 5A (typical current limit 6A) Protection: IP20

147 x 123 x 86 mm

Approx. 0.8 kg



Battery Charger,



·	The DCP2 can be applied as battery charger or as a universal DC voltage supply.	The DCP2 can be applied as battery charger or as a universal DC voltage supply.
	1 x 230V AC ±15% 4763Hz	1 x 230V AC ±15% 4763Hz
	24V DC (adjustable 23.527.5V DC)	12V DC (adjustable 11.813.8V DC)
	5A (typical current limit 6A)	10A (typical current limit 12.5A)
	IP20	IP20
	147 x 123 x 86 mm	205 x 123 x 86 mm
	Approx. 0.8 kg	Approx. 1.2 kg

	Battery Charger, DCP2-2410	Battery Charger, DCP2-2420	Battery Charger, DCP2-2420
	DCP-2 2410 24V10A Power DGP-2 2410 24V10A Power DAMPA TABLESSE A Manufacture of content A	DCP-2 2420 24V/20A Power DCP-1 2420 24V/20A Power Dottel T17A-13MA A manufacturements	DCP-2 2420 24V/20A Pometr Open 11022207. C C C C C C C C C C C C C C C C C C C
Main function:	The DCP2 can be applied as battery charger or as a universal DC voltage supply.	The DCP2 can be applied as battery charger or as a universal DC voltage supply.	The DCP2 can be applied as battery charger or as a universal DC voltage supply.
Input voltage:	1 x 115V AC ±15% 1 x 230V AC ±15% 4763Hz	1 x 230V AC ±15% 4763Hz	3 x 400/480V AC ±15% 4763Hz
Output voltage:	24V DC (adjustable 23.527.5V DC)	24V DC (adjustable 23.527.5V DC)	24V DC (adjustable 23.527.5V DC)
Output current:	10A (typical current limit 12.5A)	20A (typical current limit 25A)	20A (typical current limit 25A)
Protection:	IP20	IP20	IP20
Size:	205 x 123 x 86 mm	240 x 153 x 86 mm	240 x 153 x 86 mm
Weight:	Approx. 1.2 kg	Approx. 1.9 kg	Approx. 1.9 kg

Switchboard Instrumentation 4921240286C, page 1 of 2

Battery Charger,	,		
DCP2-2440			



The DCP2 can be applied as battery charger or as a universal DC voltage Main function:

supply.

3 x 400/480V AC ±15% 47...63Hz Input voltage:

Output voltage:

24V DC (adjustable 23.5...27.5V DC)

IP20

Output current: 40A

(typical current limit 45A)

Protection:

Size: 292 x 185 x 130 mm

Weight: Approx. 3.6 kg