Rectifier System EPOS Compact XC6-80kW



EPOS Compact rectifier system has been designed to provide uninterrupted DC power for demanding industry and telecom applications with both 24V and 48V.

EPOS Compact is a system based on Compact XCRM-series rectifier modules and equipped with a digital supervisor.

EPOS Compact system consists of system cabin C6, rectifier shelfs, mains -and battery connection unit, DC-distribution units and space of several options.



XCRM 5000 (rectifier module)	Connection 230VAC 47-63Hz Constant current for voltage range 48V 100A
Epos Compact XC6 (cabin model)	Connection: 230/400 VAC 16 * XCRM 5000 4 * Battery connection (max) 2 * DC-distribution units (max) 4 * NH 3 fuse (option) (for load) or 2 * load switch (option) 1 * LVD (option) 1 * PLD (option) TS (option)
	w:800mm h:2000mm d:600mm
Earthing	System is designed to be earthened at the positive busbar
DC-distribution unit	Place for 35 pcs MCB (2-63A) or Place for 17 pcs NH fuse
PLD	Partial Load Disconnection unit for DC-distribution
LVD	Low Voltage Disconnection unit for battery
TS	Temperature Sensor
Controller	Charge methods, battery tests, measurements, controls, data saving and communications (rj 45)
Approvals	CE CB