

<寧靜型>吸收式消音器

Silencer Selection

Call Silex for immediate assistance in selecting the appropriate silencer that best suits your application's acoustical and backpressure requirements or consult the silencer selection guide in our catalogue. You can also use Silex's exclusive Silencer Sizing and Selection Program "Silex Digital Engineer" found on the Company's secure website at www.silex.com.

Application & Performance

The GENYC series of silencers are absorptive low pressure drop low profile silencers with good high frequency performance. The silencer is manufactured from medium gauge steel, insulated, fully welded and finished with high temperature paint. A drain is included as a standard component on the silencer.

Dimensions

Model	A	B	F	G	H	Wgt.
GENYC-1.5	1.5	6 (152)	3.5 (89)	6.0 (152)	25 (635)	25 (11)
GENYC-2	2	6 (152)	3.5 (89)	6.0 (152)	30 (762)	26 (12)
GENYC-2.5	2.5	8 (203)	3.5 (89)	7.0 (178)	33 (838)	35 (16)
GENYC-3	3	9 (229)	4.0 (102)	7.5 (191)	39 (991)	41 (19)
GENYC-3.5	3.5	10 (254)	4.5 (114)	8.0 (203)	43 (1092)	56 (25)
GENYC-4	4	10 (254)	7.0 (178)	9.0 (229)	44 (1118)	60 (27)
GENYC-5	5	12 (305)	7.5 (191)	10.0 (254)	56 (1422)	101 (46)
GENYC-6	6	14 (356)	8.0 (203)	11.0 (279)	62 (1575)	111 (50)
GENYC-8	8	16 (406)	9.0 (229)	12.0 (305)	72 (1829)	160 (73)
GENYC-10	10	18 (457)	10.0 (254)	13.0 (330)	82 (2083)	205 (93)
GENYC-12	12	22 (559)	12.0 (305)	15.0 (381)	92 (2337)	350 (159)
GENYC-14	14	26 (660)	16.0 (406)	18.0 (457)	103 (2616)	558 (253)
GENYC-16	16	30 (762)	19.0 (483)	20.0 (508)	115 (2921)	721 (327)
GENYC-18	18	36 (914)	21.0 (533)	23.0 (584)	127 (3226)	875 (397)

Exposed Insulation Inside

Options

- Aluminized steel, 304, 316 or 316L stainless steel, Corten Steel
- Dual inlet or Custom inlet/outlet configurations
- Thermal insulation blankets to suit all configurations
- Mounting brackets, gussets and lifting lugs

Metric dimensions rounded to nearest mm.

Dimensions and weights are nominal and may vary slightly in production models.

The inlet and outlet on silencers up to 3½" are

Sch. 40 NPT pipe. On silencers 4" and larger the inlet and discharge are flanged, manufactured from minimum ½" thick plate and drilled to ANSI class 150.



誥鑫企業有限公司
ARITH COMPANY LTD.
 地址：台北市復興北路427巷30號
 電話：(02)2717-5038
 傳真：(02)2717-5039
 e-mail: taipei@arith.com.tw
 網址：http://www.arith.com.tw




Lit-0044 07-10

GENYC Series

25 - 30 dBA

Critical Grade
Low Profile

Typical Attenuation Curve



Typical Orientations

