

NEW

C192PF8

Power Factor Manager



Introducing the new line of
Power Factor Controllers and Powermeters

- Dual power factor
- Controls up to 8 capacitor banks
- Phase failure protection
- Harmonic and low voltage protection
- Multi-purpose switches

 **SATEC**
Powerful Solutions



NEW


C192PF8



- Bright LED displays (three windows, up to 45 pages) with adjustable display update time and automatic scrolling
- Percent load LED bar graph
- Alarm LED indicator (setpoint programmable)
- Communication LED indicators
- 8 programmable relays for alarm / setpoint / energy pulsing
- 16 programmable setups for alarm / control / trip functions
- Failsafe relay operation
- Digital input for status or external synchronization
- 4 counters operated and released by user-defined triggers
- RS-485 communications (RS-232 optional), ASCII/Modbus protocols, assignable registers
- Optically isolated programmable analog output 0-20 mA / 4-20 mA (option)
- Demands: predicted, sliding, accumulated, maximum
- Energies: import, export, net (active and reactive energy)
- Compact size: 144 x 144 mm.



Ordering Information



Programmable Analog Output

- 0 No Analog Output
A2 0 - 20 mA
A4 4 - 20 mA

* Standard

Example: C192PF8 - 0 - 5 - ACDC - 0 - A2

BB0084 Rev. A1

Class 0.5 Accuracy

Parameter	Reading %	Full Scale %
Voltage		0.3
Line current		0.3
Active power		0.4
Reactive power		0.4
Apparent power		0.4
Power factor		1
Frequency	0.02	
Neutral (unbalanced) current		0.6
Ampere demand		0.3
kW demand	same as for kW	
kVA demand	same as for kVA	
Active energy import & export	same as for power	
Reactive energy import & export	same as for power	
Apparent energy	same as for power	

Measurement error is typically much less than the maximum error specified here.



詒鑫企業有限公司
ARITH COMPANY LTD.
地址：台北市105復興北路427巷30號
電話：(02) 2717-5038 (代表號)
傳真：(02) 2717-5039
郵件：taipei@arith.com.tw
網址：www.arith.com.tw